

Patriot Dock Brace Kit Instructions PN 10828

Parts List:

- (2) Tubular Braces, 5 ft long
- (2) U-Bolt Clamps
- (2) Bolt/Nut/Washers, 3/8 diameter

Application: The Brace Kit is intended to provide additional stability in one direction to pipe supports on the deep end of the dock. The Brace Kit is especially important for rolling your patriot dock into and out of the water in deep water situations where long pipe supports are used and in situations where the lake bottom is soft and mucky.

Assembly instructions:

Attach one end of the brace to the lowest 3/8 diameter hole in the Patriot Dock frame 4 feet from the pipe to be supported using the bolt provided in the kit. The shank of the bolt and the nut should be point toward inside the dock frame.

Disassemble the U-Bolt clamp and thread the U-Bolt through the hole on the other end of the brace and install fit the U-Bolt to the support pipe at a distance approximately 3 feet from the bottom of the frame. Point the shanks of the U-Bolts toward the dock frame or away from the swimming area if possible. Tighten the nuts on both ends of the brace.

Repeat the above steps for the pipe supports on the other side of the dock.

Caution: It is important to direct the shank end of the bolts away from the swimming area (especially ladders attached to the dock) to make sure the bolt ends do not cause injury to swimmers.

US Dock and Hardware LLC
Harris, MN

www.usdockandhardware.com www.patriotdocks.com

(651)674-2450